

DAIKIN SPLIT TYPE WALL MOUNTED AIR CONDITIONERS							
Model	Indoor unit	FTKS25DVM	FTKS35DVM	FTKS50GVMG	FTKS60GVMG	FTKS71HVMG	
Name	Outdoor unit	RKS25GVMG	RKS35GVMG	RKS50GVMG	RKS60GVMG	RKS71HVMG	
Capacity	Rated (Min.-Max.)	kW	2.5 (1.2-3.2)	3.5 (1.4-4.0)	5.0 (1.7-6.0)	6.0 (2.3-6.7)	7.1 (2.3-8.5)
		Btu/h	8,500 (4,050-10,900)	11,900 (4,750-13,650)	17,100 (5,800-20,500)	20,500 (7,800-22,900)	24,200 (7,800-29,000)
Power supply			1 phase, 230V, 50Hz				
Running current	Rated	A	3.9	4.8	6.2	7.8	9.2
Power consumption	Rated (Min.-Max.)	W	700 (295-1,050)	1,035 (300-1,400)	1,400 (440-2,080)	1,780 (570-3,580)	2,100 (570-3,100)
COP	Rated	W/W	3.57	3.38	3.57	3.37	3.38
Indoor unit		FTKS25DVM	FTKS35DVM	FTKS50GVMG	FTKS60GVMG	FTKS71HVMG	
Front panel colour		White					
Airflow rate (H)	mx3/min (cfm)	8.7 (307)	8.9 (314)	14.7 (519)	17.4 (614)	21.5 (760)	
Fan speed		5 Steps, quiet and automatic					
Sound Levels (H/L/SL)	dB (A)	37/25/22	39/26/23	43/34/31	46/37/34		
Dimensions (H x W x D)	mm	283 x 800 x 195		290 x 1,050 x 238		340 x 1,200 x 240	
Machine weight	kg	9		12		17	
Outdoor unit		RKS25GVMG	RKS35GVMG	RKS50GVMG	RKS60GVMG	RKS71HVMG	
Casing colour		Ivory white					
Compressor	Type	Hermetically sealed swing type					
	Motor output	W	600		1,100	1,920	
Refrigerant charge (R410A)	kg	0.8	1	1.5	1.7	2.3	
Sound Level (H/L)	dB (A)	46/43	47/44		47/44	54/49	52/49
Dimensions (H x W x D)	mm	550 x 765 x 285		735 x 825 x 300		770 x 900 x 320	
Machine weight	kg	32	34	47	55	71	
Operation range	CDB	10 to 46					
	Liquid	mm	6.4			9.5	
Piping connections	Gas	mm	9.5		12.7	15.9	
	Drain	mm	18.0				
Max. piping length	m	25			30		
Max.height difference	m	15			20		
ESTIMATED PRICE							
SYSTEM 1--9K BTU (MODEL: FTKS25DVM/RKS25GVMG)		\$1,100.00					
SYSTEM 1--12K BTU (MODEL: FTKS35DVM/RKS35GVMG)		\$1,250.00					
SYSTEM 1--18K BTU (MODEL: FTKS50GVMG/RKS50GVMG)		\$1,950.00					
SYSTEM 1--21K BTU (MODEL: FTKS60GVMG/RKS60GVMG)		\$2,250.00					
SYSTEM 1--24K BTU (MODEL: FTKS71HVMG/RKS71HVMG)		\$2,450.00					
DAIKIN SUPER MULTI TYPE WALL MOUNTED AIR CONDITIONERS							
Indoor unit		FTKS25DVM	FTKS35DVM	FTKS50FVM	FTKS60FVM	FTKS71FVM	
Power supply		1 phase, 220-240 V/220-230 V, 50/60 Hz					
Front panel colour		White					
Airflow rate (H)	mx3/min (cfm)	8.7 (307)	8.9 (314)	14.7 (519)	16.2 (572)	17.4 (614)	
Fan speed		5 Steps, quiet and automatic					
Sound Levels (H/L/SL)	dB (A)	37/25/22	39/26/23	43/34/31	45/36/33	46/37/34	
Temperature control		Microcomputer control					
Dimensions (H x W x D)	mm	283 x 800 x 195		290 x 795 x 238		290 x 1,050 x 238	
Machine weight	kg	9		12			
Piping connections	Liquid (flare)	6.4					
	Gas (flare)	9.5		12.7		15.9	
	Drain	18.0					
Heat insulation		Both liquid and gas pipes					
Outdoor unit		3MKS50FSG	3MKS71FSG	4MKS80FSG			
Cooling capacity (kW) Rated (Min-Max)		4.8 (1.95-7.07)	6.9 (3.01-8.82)	7.3 (3.3-10.50)			
Power supply		1 phase, 230 V, 50 Hz					
Casing colour		Ivory white					
Compressor type		Hermetically sealed swing type					
Sound Level	dB (A)	46/43*1	48/45*1				
Dimensions (H x W x D)	mm	735 x 826 (+110*2) x 300		770 x 900 x 320			
Machine weight	kg	49	58	69			
Operation range	CDB	10 to 46					
Max. piping length	m	50 (total)	60 (total)	70 (total)			
		25 (for each room)					
Necessity of additional charge	g/m	chargeless					
Max.installation height difference	m	15 (between indoor and outdoor units)					
ESTIMATED PRICE							
SYSTEM 2--9K + 9K BTU (MODEL: FTKS25DVM x2/3MKS50FSG)		\$2,400.00					
SYSTEM 2--12K + 9K BTU (MODEL: FTKS35DVM/FTKS25DVM/3MKS50FSG)		\$2,500.00					
SYSTEM 2--18K + 9K BTU (MODEL: FTKS50FVM/FTKS25DVM/3MKS71FSG)		\$3,100.00					
SYSTEM 2--24K + 9K BTU (MODEL: FTKS71FVM/FTKS25DVM/4MKS80FSG)		\$3,550.00					
SYSTEM 3--9K + 9K + 9K BTU (MODEL: FTKS25DVM x3/3MKS71FSG)		\$3,100.00					
SYSTEM 3--12K + 9K + 9K BTU (MODEL: FTKS35DVM/FTKS25DVM x2/3MKS71FSG)		\$3,250.00					
SYSTEM 3--18K + 9K + 9K BTU (MODEL: FTKS50FVM/FTKS25DVM x2/4MKS80FSG)		\$3,650.00					
SYSTEM 3--24K + 9K + 9K BTU (MODEL: FTKS71FVM/FTKS25DVM x2/4MKS80FSG)		\$3,800.00					
SYSTEM 4--18K + 9K + 9K+9K BTU (MODEL: FTKS50FVM/FTKS25DVM x3/4MKS80FSG)		\$4,000.00					
SYSTEM 4--24K + 9K + 9K+9K BTU (MODEL: FTKS71FVM/FTKS25DVM x3/4MKS80FSG)		\$4,300.00					